


## J CAP PROFILES

### ARCHITECTURAL ALUMINUM J CAPS - FOR .3125" TO .750" MATERIAL

Our aluminum J caps have a high resistance to corrosion and are easy to machine, cut, form or weld. All our extruded aluminum J channels have a high strength-to-weight ratio, are resistant to stress cracks, and are non-magnetic.

- Stocked in Lengths: Varies by individual profile
- Stocked in Finishes: Varies by individual profile
- Composition: Varies by individual profile



#### ITEM NUMBERS & DIMENSIONS

ITEM	A	B	C	D	ALLOY
JCP-402 (E-402)	0.313	0.375	0.448	0.875	6560-T42 / 6063-T5
JCP-814 (E-814)	0.340	0.375	0.420	0.875	6063-T6
JCP-5240 (E-5240)	0.375	0.375	0.527	0.875	6063 ALLOY
JCP-400 (E-400)	0.375		0.516	0.750	6463-T5
JCP-2465 (E-2465)	0.390	0.438	0.495	0.906	6063-T5
JCP-1998 (E-1998)	0.500	0.375	0.664	1.000	6063-T5
JCP-2627 (EAM-2627)	0.500	0.500	0.650	1.500	6063-T6
JCP-3520 (EAM-3520)	0.500	0.500	0.650	1.500	6063-T6
JCP-2207 (EAM-2207)	0.750	0.250	1.125	1.625	6063-T5
JCP-2560 (E-2560)	0.750	0.500	0.895	1.250	6063-T6
JCP-2231 (EAM-2231)	0.875	0.312	1.055	1.000	6063-T6

## FINISH OPTIONS

Eagle Aluminum offers a variety of standard finishes as well as customized anodized finishes to help create the exact look you need. Custom aluminum finishes are available in anodized, mechanical, or painted finishes.

### STANDARD ANODIZED FINISHES



Clear Satin  
AB1010

Champagne  
AB1020

Golden Bronze  
AB1030

Light Bronze  
AB1040

Medium Bronze  
AB1050

Dark Bronze  
AB1060

Deep Bronze  
AB1070

Black  
AB1080

### POWDER COAT FINISHES



White  
PM5210

Cream  
PM5220

Almond  
PM5230

Khaki  
PM5240

Silver Gray  
PM5250

Light Gray  
PM5260

Dark Gray  
PM5270

Medium Bronze  
PM5050

Dark Bronze  
PM5060

Black  
PM5080

### FIELD PAINTING INSTRUCTIONS

Clean and prep mill finish (MF) trim in accordance with the paint manufacturer's best practices. Ensure paint and primer is recommended for aluminum via paint manufacturer. Apply coating until desired finish is achieved.

**Painting Clear Anodized:** This is generally not recommended, but can be achieved when necessary. Clean and treat aluminum with an acid etch solution. Rinse thoroughly and dry. Apply an acid-etched prime/primer based on the paint manufacturer's best practices. Apply paint coating per paint manufacturer's specifications.

### CUTTING INSTRUCTIONS

When necessary, cut material using a miter saw with a high-quality, non-ferrous carbide blade with a minimum tooth count of 80, and lubricant. Clean trim prior to installation. Refer to saw blade manufacturer's best practices for additional information.

### WARRANTY

Eagle Aluminum's warranty covers manufacturing defects for a period of three years. Refer to Eagle Aluminum's warranty documentation for additional details.